



Residual current operated circuit breaker, 2-pole, Type A, In: 25A, 300mA, Un AC: 230V Residential

Model	
product brand name	SENTRON
product designation	RCCB
design of the product	Instantaneous
General technical data	
number of poles	2
size of installation devices / according to DIN 43880	1
mechanical service life (switching cycles) / typical	3 000
short-circuit current / of series fuse / maximum permissible	63 A
short-circuit current rating	6 kA
switching function / short-term delayed	No
overvoltage category	III
Supply voltage	
supply voltage / for testing equipment / minimum	100 V
value range / of the supply voltage frequency	50 Hz
value range / of the operating frequency	50 Hz
value range / of the supply voltage / at AC	230/400 V
Protection class	
protection class IP	IP20, if the distribution board is installed, with connected conductors
Switching capacity	
switching capacity current	
<ul style="list-style-type: none"> <li>according to IEC 61008-1 / rated value</li> </ul>	0.5 kA
Dissipation	
power loss [W]	
<ul style="list-style-type: none"> <li>for rated value of the current / at AC / in hot operating state / per pole</li> </ul>	1 W
<ul style="list-style-type: none"> <li>maximum</li> </ul>	2 W
Current	
tripping fault current / rated value	300 mA
operational current	
<ul style="list-style-type: none"> <li>at 40 °C / rated value</li> </ul>	25 A
<ul style="list-style-type: none"> <li>at AC / rated value</li> </ul>	25 A
residual current type	A
let-through current / permissible	5 200 A
I <sup>2</sup> t value / permissible	58 000 A <sup>2</sup> ·s
surge current resistance / rated value	1 kA
Product details	
product feature / silicon-free	Yes
product extension / installable / supplementary devices	No

Connections	
connectable conductor cross-section / solid	
• minimum	0.75 mm <sup>2</sup>
• maximum	35 mm <sup>2</sup>
connectable conductor cross-section / stranded	
• minimum	0.75 mm <sup>2</sup>
• maximum	35 mm <sup>2</sup>
tightening torque / with screw-type terminals	
• minimum	2.5 N·m
• maximum	3 N·m
position / of power supply cord	top or bottom

Mechanical Design	
height	90 mm
width	36 mm
depth	70 mm
installation depth	70 mm
number of modular width units	2
fastening method	DIN rail (REG)
mounting position	any
net weight	192 g

Environmental conditions	
ambient temperature / during operation	
• minimum	-5 °C
• maximum	45 °C
ambient temperature / during storage	
• minimum permissible	-40 °C
• maximum permissible	75 °C
number of test cycles / for environmental testing / according to IEC 60068-2-30	28

<b>General Product Approval</b>	<b>other</b>	<b>Dangerous Good</b>
---------------------------------	--------------	-----------------------

[Confirmation](#)



[Miscellaneous](#)

[Transport Information](#)

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SV5612-6>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5SV5612-6>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SV5612-6](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV5612-6)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



